



DESIGN

Product Type:	Broadloom-Custom
Construction:	Tufted
Minimum Sq. Yd.:	500 sq yd minimum
Surface Texture:	Textured Patterned Cut & Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Dye Method:	Solution Dyed
Backing Material:	Unibond® Plus
Fiber Type:	Colorstrand® SD Nylon
Face Weight:	36.0 oz. per sq. yd. (1221 g/m2)
Pattern Repeat:	144" (W) x 54.5" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Soil Stain Protection

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 3802
NSF 140:	Gold

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Unibond® Plus Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	---



958
Oxford



938
Navarino Smoke



948
Castor



934
London Dust



926
Ester Hazy



851
Congo



723
Tourterelle



848
Havannah



131
Apollo