

Social Harmony Collection



DESIGN

Product Type:	Resilient Sheet
Gauge:	.086" (2.18mm)
Wear Layer:	16 mil (0.4mm)
Finish:	M-Force 1" Enhanced Urethane
Pattern Repeat:	(39.37x39.17): 133, 890 (no drop), 148, 928 (19.69" drop); (39.37x39.37) 879, 948 (13.12" drop); (47.24x39.37) 828 (1/2 drop)
Size:	12' width (3.66m)
Roll Size:	59' min - 130' max
Seaming Method:	Cold Weld
Installation Method:	Do not reverse sheet for installation
Recommended Adhesive:	Mohawk M95.0 Adhesive or MS160 Spray AdhesiveMohawk

PERFORMANCE


Construction:	Commercial Grade Heterogeneous Resilient Sheet Non-ortho Phthalate Construction
Classification:	ASTM F-1303 Type 1, Grade 1, Class A
Thickness:	ASTM F-386 - Passes - Nominal ± 0.005 in.
Flexibility:	ASTM 137- Passes - 6mm Mandrel
Residual Indentation:	ASTM F-1914 - Passes - Average less than 8%
Resistance To Chemicals:	ASTM F-925 - Passes
Resistance To Light:	ASTM F-1515 - Passes - ΔE ≤ 8
Resistance To Heat:	ASTM F-1514 - Passes - ΔE ≤ 8
Critical Radiant Flux:	ASTM E-648 - Passes - ≥ 0.45 watts/cm ² , Class 1
Smoke Density:	ASTM E-662 - Passes
Dynamic Rolling Load:	ASTM 2753- Passes - 500 Cycles no Change
Electro Static Propensity:	AATCC 134 - Passes - Average .5 kv Positive
Wear Layer Thickness:	ASTM 410 - Passes - .55mm avg.

SUSTAINABILITY


Certification:	FloorScore® certified
----------------	-----------------------

SERVICE


Warranties:	Limited 10 Year Light Commercial
-------------	----------------------------------




890
Master View



133
Fresh Cut




948
Lake Effect



879
Strong Rods



148
Clean Slate



928
Open Sky



828
Rich Layer