

### DESIGN

Product Type:	Resilient Sheet
Overall Thickness:	.086" (2.18 mm)
Wear Layer:	16 mil (0.4 mm)
Finish:	Enhanced Urethane
Pattern Repeat:	(39.37x39.37)
Size:	12' width (3.66m)
Roll Size:	59' min - 130' max
Seaming Method:	Cold Weld
Installation Method:	Do not reverse sheet for installation
Recommended Adhesive:	Mohawk M95.0 Adhesive or MS160 Spray AdhesiveMohawk

### PERFORMANCE


Construction:	Commercial Grade Heterogeneous Resilient Sheet
Classification:	ASTM F-1303 Type 1, Grade 1, Class A
Thickness:	ASTM F-386 - Passes - Nominal $\pm 0.005$ in.
Flexibility:	ASTM 137- Passes - 6mm Mandrel
Residual Indentation:	ASTM F-1914 - Passes - Average less than 8%
Resistance To Chemicals:	ASTM F-925 - Passes
Resistance To Light:	ASTM F-1515 - Passes - $\Delta E \leq 8$
Resistance To Heat:	ASTM F-1514 - Passes - $\Delta E \leq 8$
Critical Radiant Flux:	ASTM E-648 - Passes - $\geq 0.45$ watts/cm <sup>2</sup> , Class 1
Smoke Density:	ASTM E-662 - Passes
Dynamic Rolling Load:	ASTM 2753- Passes - 500 Cycles no Change
Electro Static Propensity:	AATCC 134 - Passes - Average .5 kv Positive
Wear Layer Thickness:	ASTM 410 - Passes - .55mm avg.
Static Coefficient of Friction:	ASTM C-1028 - Passes

### SUSTAINABILITY


Certification:	FloorScore® certified
Certification Detail:	May contribute to or comply with LEED® credits
Country of Origin:	Made In USA with content from the Americas and Europe

### SERVICE

Warranties:	Limited 10 Year Light Commercial
-------------	----------------------------------



153  
Sunshine In



929  
Silver Linings