

Social Harmony Collection



DESIGN

Product Type:	Resilient Sheet
Gauge:	.086" (2.18mm)
Wear Layer:	16 mil (0.4mm)
Finish:	M-Force 1" Enhanced Urethane
Pattern Repeat:	(47.24x47.24) 878 (1/2 drop); (47.24x39.37): 183, 163, 853, 868 (1/2 drop) 968, 173 (19.69" drop)
Size:	12' width (3.66m)
Roll Size:	59' min - 130' max
Seaming Method:	Cold Weld
Installation Method:	Do not reverse sheet for installation
Recommended Adhesive:	Mohawk M95.0 Adhesive or MS160 Spray Adhesive Mohawk

PERFORMANCE


Construction:	Commercial Grade Heterogeneous Resilient Sheet
Classification:	ASTM F-1303 Type 1, Grade 1, Class A
Thickness:	ASTM F-386 - Passes - Nominal ± 0.005 in.
Flexibility:	ASTM 137- Passes - 6mm Mandrel
Residual Indentation:	ASTM F-1914 - Passes - Average less than 8%
Resistance To Chemicals:	ASTM F925 - Passes
Resistance To Light:	ASTM F-1515 - Passes - ΔE ≤ 8
Resistance To Heat:	ASTM F-1514 - Passes - ΔE ≤ 8
Critical Radiant Flux:	ASTM E-648 - Passes - ≥ 0.45 watts/cm ² , Class 1
Smoke Density:	ASTM E-662 - Passes
Dynamic Rolling Load:	ASTM 2753- Passes - 500 Cycles no Change
Electro Static Propensity:	AATCC 134 - Passes - Average .5 kv Positive
Wear Layer Thickness:	ASTM 410 - Passes - .55mm avg.
Static Coefficient of Friction:	ASTM C-1028 Passes

SUSTAINABILITY


Certification:	FloorScore® certified
Certification Detail:	May contribute to or comply with LEED® credits
Country of Origin:	Made In USA

SERVICE


Warranties:	Limited 10 Year Light Commercial
-------------	----------------------------------




163
Soaring




173
Vista Scape



183
Finishing Touch



853
Focal Point



868
Taking Shape



878
Spring Awakening



968
Sky High