



DESIGN

Product Type:	Resilient Sheet
Gauge:	.086" (2.18mm)
Wear Layer:	16 mil (0.4mm)
Finish:	M-Force 1" Enhanced Urethane
Size:	12' width (3.66m)
Anti-Microbial:	No
Installation:	Do not reverse sheet for installation
Recommended Adhesive:	Mohawk M95.0 Adhesive or MS160 Spray AdhesiveMohawk

PERFORMANCE


Construction:	Commercial Grade Heterogeneous Resilient Sheet
Classification:	ASTM F-1303 Type 1, Grade 1, Class A
Smoke Density:	ASTM E-662 - Passes
Thickness:	ASTM F-386 - Passes - Nominal ± 0.005 in.
Flexibility:	ASTM 137- Passes - 6mm Mandrel
Residual Indentation:	ASTM F-1914 - Passes - Average less than 8%
Resistance To Heat:	ASTM F-1514 - Passes - ΔE ≤ 8
Resistance To Light:	ASTM F-1515 - Passes - ΔE ≤ 8
Critical Radiant Flux:	ASTM E-648 - Passes - ≥ 0.45 watts/cm ² , Class 1

SUSTAINABILITY

Certification:	FloorScore® Certified
----------------	-----------------------

SERVICE


Warranties:	Limited 10 Year Light Commercial
-------------	----------------------------------




163
Soaring




183
Finishing Touch



853
Focal Point



173
Vista Scape



868
Taking Shape



878
Spring Awakening



968
Sky High