



**DESIGN**

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	8,571
Weight Density:	171,428
Stitches Per Inch:	11.4 (44.88 per 10 cm)
Finished Pile Thickness:	.084" (2.13 mm)
Dye Method:	Solution Dyed
Backing Material:	EcoFlex NXT
Fiber Type:	Duracolor® Premium Nylon
Face Weight:	20.0 oz. per sq. yd. (678 g/m <sup>2</sup> )
Pattern Repeat:	Not Applicable
Size:	12" x 36" (.3048 m x .9144 m)
Installation Method:	Monolithic, HalfLap, BrickAshlar, BasketWeave, PlankHalfLap, MonolithicStepping, Random, Herringbone
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Severe

**SUSTAINABILITY**


IAQ Green Label Plus:	Green Label Plus 1171
Pre-Consumer Recycled Content:	55%
Post-Consumer Recycled Content:	1%
NSF 140:	Gold
Declare Label:	Declared Red List Free

**PERFORMANCE**


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

**SERVICE**

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static
-------------	---



138  
Sulpher



576  
Lagoon




739  
Glacier




856  
Sediment




869  
Alpine



949  
Fossil



955  
Coastal



978  
Mineral