



**DESIGN**

Tufted Pile Weight:	20.0 oz. per sq. yd. (678 g/m <sup>2</sup> )
Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	7,272
Weight Density:	145,454
Stitches Per Inch:	11.2 (44.09 per 10 cm)
Finished Pile Thickness:	.099" (2.51 mm)
Dye Method:	Solution Dyed
Backing Material:	EcoFlex NXT
Fiber Type:	Duracolor® Premium Nylon
Fiber Technology:	Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet.
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	Quarter Turn, Monolithic, Brick Ashlar, Vertical Ashlar, Multi Directional
GSA Stain Release Rating:	Pass
Stain Release Technology:	Permanent, Built into Fiber
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Severe



138  
Sulpher



576  
Lagoon



739  
Glacier



856  
Sediment



869  
Alpine



949  
Fossil



955  
Coastal



978  
Mineral

**SUSTAINABILITY**

IAQ Green Label Plus:	CRI Green Label Plus GLP1171
Pre-Consumer Recycled Content:	55%
NSF 140:	EcoFlex NXT - NSF 140 Gold
Declare Label:	Declared Red List Free

**PERFORMANCE**

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

**SERVICE**

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static
-------------	---