



DESIGN

Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Cut & Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	9,679
Weight Density:	275,858
Stitches Per Inch:	10.0 (39.37 per 10 cm)
Finished Pile Thickness:	.106" (2.69 mm)
Dye Method:	Solution Dyed
Backing Material:	Unibond® Plus
Fiber Type:	Colorstrand® SD Nylon
Face Weight:	28.5 oz. per sq. yd. (966 g/m2)
Pattern Repeat:	3" (w) x 6.5" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 3802
Pre-Consumer Recycled Content:	39%
NSF 140:	Gold
Declare Label:	Declared Red List Free

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	Lifetime Limited Unibond® Plus Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	---



141
Overlay




365
Poplin



553
Trim



641
Stitches



858
Blending



859
Thimble



869
Gather



889
Facing



945
Thread



948
Binding



965
Needle



989
Pique