



DESIGN

Tufted Pile Weight:	28.5 oz. per sq. yd. (966 g/m2)
Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Cut & Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	9,679
Weight Density:	275,858
Stitches Per Inch:	10.0 (39.37 per 10 cm)
Finished Pile Thickness:	.106" (2.69 mm)
Dye Method:	Solution Dyed
Backing Material:	Unibond® Plus
Fiber Type:	Colorstrand® SD Nylon
Pattern Repeat:	3" (w) x 6.5" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY

IAQ Green Label Plus:	CRI Green Label Plus GLP3802
Pre-Consumer Recycled Content:	39%
NSF 140:	Unibond Plus - NSF 140 Gold
Declare Label:	Declared Red List Free

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	Lifetime Limited Unibond® Plus Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	---



141
Overlay
Quickship Available



365
Poplin
Quickship Available



553
Trim
Quickship Available



641
Stitches
Quickship Available



858
Blending
Quickship Available



859
Thimble
Quickship Available



869
Gather
Quickship Available



889
Facing
Quickship Available



945
Thread
Quickship Available



948
Binding
Quickship Available



965
Needle
Quickship Available



989
Pique
Quickship Available