



**DESIGN**

---

Product Type:	Commercial Laminate
Gauge:	15/32" (12mm)
Finish:	AC4 rated wear surface with aluminum oxide
Size:	5 1/4" W x 47 1/4" L
Anti-Microbial:	No
Installation:	Uniclic® Locking System
Recommended Adhesive:	None Required
Square Feet Per Carton:	13.75 sq. ft. per ctn
Underlayment:	Float over SilentGuard underlayment (no adhesive required)

**PERFORMANCE**

---

Construction:	Commercial Laminate
Classification:	NALFA/ANSI LF-01-2011
Smoke Density:	ASTM E662 - Passes - < 450
Thickness:	Meets or Exceeds NALFA Level 4
Static Load:	Meets or Exceeds NALFA Level 4
Resistance To Light:	Meets or exceeds NALFA Level 4
Critical Radiant Flux:	ASTM E648 - Passes - Class 1

**SUSTAINABILITY**


---

Certification:	FloorScore® Certified
----------------	-----------------------


**SERVICE**

---


Warranties:	Limited 5 Year Light Commercial
-------------	---------------------------------




10  
Crisp Autumn Oak



04  
Sunbeam Acacia



12  
Soft Copper Oak



14  
Honey Blonde  
Maple