

In The Groove Collection



DESIGN

Product Type:	Commercial Laminate
Gauge:	15/32" (12mm)
Finish:	AC4 rated wear surface with aluminum oxide
Size:	7 1/2" W x 54 11/32" L
Square Feet Per Carton:	16.93 sq. ft. per ctn
Format:	Single plank design with micro-beveled edges/ends
Core:	HDF (High Density Fiberboard)
Trim and Moldings:	Color coordinating trims and moldings; multi-purpose 5-in-1 molding (t-molding, square nose, carpet reducer, hard surface reducer, stair nose) and quarter round
Installation Method:	Uniclic® Locking System
Recommended Adhesive:	None Required
Underlayment:	Float over SilentGuard underlayment (no adhesive required)
Grade Level:	On, Above or Below Grade

PERFORMANCE


Construction:	Commercial Laminate
Classification:	NALFA/ANSI LF-01-2011
Thickness:	Meets or Exceeds NALFA Level 4
Static Load:	Meets or Exceeds NALFA Level 4
Resistance To Light:	Meets or exceeds NALFA Level 4
Stain Resistance:	Meets or exceeds NALFA Level 4
Critical Radiant Flux:	ASTM E648 - Passes - Class 1
Smoke Density:	ASTM E662 - Passes - < 450
Wear Resistance:	Meets or exceeds NALFA Level 3 - AC4 rated wear surface
Caster Chair Resistance:	Meets or exceeds NALFA Level 4
Large Ball Impact Resistance:	Meets or exceeds NALFA Level 4
Small Ball Impact Resistance:	Meets or exceeds NALFA Level 4
Static Coefficient of Friction:	ADA Compliant; 0.6 Dry

SUSTAINABILITY


Certification:	FloorScore® certified
CARB II Compliant:	Yes
NALFA Certified:	Yes

SERVICE


Warranties:	Limited 5 Year Light Commercial
-------------	---------------------------------




01
Fawn Chestnut




03
Knotted Chestnut



04
Earthen Chestnut



05
Sandcastle Oak



06
Driftwood Oak