



DESIGN

Tufted Pile Weight:	18.0 oz. per sq. yd. (610 g/m²)
Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Heathered Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	6,230
Weight Density:	112,153
Stitches Per Inch:	7.4 (29.13 per 10 cm)
Finished Pile Thickness:	.104" (2.64 mm)
Dye Method:	Solution Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Colorstrand® SD Nylon
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	Brick Ashlar, Vertical Ashlar, Quarter Turn
Stain Release Technology:	Sentry Plus Stain Protection
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY


IAQ Green Label Plus:	CRI Green Label Plus GLP1098
Pre-Consumer Recycled Content:	48%
NSF 140:	EcoFlex ICT - NSF 140 Gold
Declare Label:	Declared

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	---



374
Terra Clay
Quickship Available



559
Anodized Lapis
Quickship Available



589
Celestial
Quickship Available




679
Blarney Stone
Quickship Available




689
Forest
Quickship Available



719
Carbon Char
Quickship Available



837
Biscotti Crunch
Quickship Available



879
Earth
Quickship Available



928
Majolica Tin
Quickship Available



948
Quartz
Quickship Available



964
Smokestack
Quickship Available



965
Steel
Quickship Available



978
Mineralite
Quickship Available



989
Onyx
Quickship Available