



DESIGN

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Heathered Loope
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	5,890
Weight Density:	106,036
Stitches Per Inch:	7.4 (29.13 per 10 cm)
Finished Pile Thickness:	.110" (2.79 mm)
Dye Method:	Solution Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Colorstrand® SD Nylon
Face Weight:	18.0 oz. per sq. yd. (610 g/m2)
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 1098
Pre-Consumer Recycled Content:	48%
NSF 140:	Gold
Declare Label:	Declared

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------



374
Terra Clay



559
Anodized Lapis



589
Celestial




679
Blarney Stone




689
Forest




719
Carbon Char



837
Biscotti Crunch



879
Earth



928
Majolica Tin



948
Quartz



964
Smokestack



965
Steel



978
Mineralite



989
Onyx