
BT400 New Basics III Tile

Mohawk Group

Mohawk Group



DESIGN

Weight Density:

Tufted Pile Weight: 18.0 oz. per sq. yd. (610 g/m2)

 Product Type:
 Tile

 Construction:
 Tufted

 Minimum Sq. Yd.:
 No Minimum

Surface Texture: Textured Heathered Loop

Gauge: 1/10 (39.37 rows per 10 cm)
Density: 6,230

Stitches Per Inch: 7.4 (29.13 per 10 cm)
Finished Pile Thickness: .104" (2.64 mm)

Dye Method: Solution Dyed

Backing Material: EcoFlex ICT

Fiber Type: Colorstrand® SD Nylon

Pattern Repeat: Not Applicable

Size: 24" x 24" (.6096 m x .6096 m)

Installation Method: Brick Ashlar, Vertical Ashlar, Quarter Turn

112,153

Stain Release Technology: Sentry Plus Stain Protection
Soil Release Technology: Sentry Soil Protection

Foot Traffic Recommendation TARR: Heavy



374 Terra Clay Quickship Available



559 Anodized Lapis Quickship Available



589 Celestial Quickship Available



679 Blarney Stone Quickship Available



689 Forest Quickship Available



719 Carbon Char Quickship Available



837 Biscotti Crunch Quickship Available



879 Earth Quickship Available



928 Majolica Tin Quickship Available

SUSTAINABILITY

IAQ Green Label Plus: CRI Green Label Plus GLP1098

Pre-Consumer Recycled Content: 48

NSF 140: EcoFlex ICT - NSF 140 Gold

Declare Label: Declared

PERFORMANCE

Static: AATCC-134 Under 3.5 KV

Flammability: ASTM E 648 Class 1 (Glue Down)

Smoke Density: ASTM E 662 Less than 450

SERVICE

Lifetime Limited Carpet Tile Warranty, Lifetime
Warranties:
Limited Colorfastness to Light, 10 Year Limited

Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static



Mohawk Group



948 Quartz Quickship Available



964 Smokestack Quickship Available



965 Steel Quickship Available



978 Mineralite Quickship Available



989 Onyx Quickship Available