

Hot and Heavy Collection



**DESIGN**

Product Type:	Floating LVT
Gauge:	.20"(5mm)
Wear Layer:	20 mil (0.5mm)
Finish:	M-Force™ Enhanced Urethane
Surface Profile:	Registered Emboss
Size:	9" x 59" (nominal)
Square Feet Per Carton:	22.4 sf/ctn (2.12 m2/ctn)
Pieces Per Carton:	6 pcs/ctn
Pounds per carton:	40.78 lbs/ctn (18.49 kg/ctn)
Installation Method:	Perimeter Glue
Recommended Adhesive:	Perimeter glue only with MS160 Spray. May also use M95.0 Resilient Flooring Adhesive

**PERFORMANCE**

Construction:	Luxury Vinyl Tile with underlay
Classification:	ASTM F-1700 - Class III, Type A - Smooth, Type B - Embossed
Squareness:	ASTM F2055 -10 Passes - maximum 0.010 in. (0.25mm)
Size and Tolerance:	ASTM F2055 - Passes - at ±0.016 in./lin. Ft. (0.4 mm/305 mm)
Thickness:	ASTM F386 - Passes - as specified ±0.005 in. (0.13 mm)
Flexibility:	ASTM F137 - Passes - 1 in. (25.4-mm mandrel, no crack or break)
Dimensional Stability:	ASTM F2199 - Passes - no greater than 0.020 in./lin. Ft. (0.51 mm/305 mm)
Static Load:	ASTM F970 - Passes – Exceeds 250 psi
Residual Indentation:	ASTM F1914 - Passes - average less than 8%
Slip Resistant:	ADA Compliant - > 0.6
Resistance To Chemicals:	ASTM F925 - Passes - no change
Resistance To Light:	ASTM F1515 - Passes - less than 8 ave., max
Resistance To Heat:	ASTM F1514 - Passes - less than 8 ave., max
Critical Radiant Flux:	ASTM E648 - Passes - > 0.45 watts/cm², Class 1
Impact Insulation Class:	57

**SUSTAINABILITY**

Certification:	FloorScore® certified
Biobased Material Content:	8%

**SERVICE**

Warranties:	Limited 10 Year Commercial
-------------	----------------------------



132 Vera



138 Kingsley



241 Knox



322 Finn



358 Jackson



628 Lenox



758 Hermes



851 Butler



853 Emerson

Hot and Heavy Collection



958  
Cole