

Hot and Heavy Collection



**DESIGN**

|                         |  |
|-------------------------|--|
| Product Type:           | Floating LVT   |
| Gauge:                  | .20" (5mm)   |
| Wear Layer:             | 20 mil (0.5mm)   |
| Finish:                 | M-Force™ Enhanced Urethane   |
| Surface Profile:        | Registered Emboss  |
| Size:                   | 9" x 59" (nominal)   |
| Square Feet Per Carton: | 22.4 sf/ctn (2.12 m2/ctn)  |
| Pieces Per Carton:      | 6 pcs/ctn  |
| Pounds per carton:      | 40.78 lbs/ctn (18.49 kg/ctn)   |
| Installation Method:    | Perimeter Glue   |
| Recommended Adhesive:   | Perimeter glue only with MS160 Spray. May also use M95.0 Resilient Flooring Adhesive |

**PERFORMANCE**

|                          |   |
|--------------------------|---|
| Construction:            | Luxury Vinyl Tile with underlay   |
| Classification:          | ASTM F-1700 - Class III, Type A - Smooth, Type B - Embossed               |
| Squareness:              | ASTM F2055 -10 Passes - maximum 0.010 in. (0.25mm)                        |
| Size and Tolerance:      | ASTM F2055 - Passes - at ±0.016 in./lin. Ft. (0.4 mm/305 mm)              |
| Thickness:               | ASTM F386 - Passes - as specified ±0.005 in. (0.13 mm)                    |
| Flexibility:             | ASTM F137 - Passes - 1 in. (25.4-mm mandrel, no crack or break)           |
| Dimensional Stability:   | ASTM F2199 - Passes - no greater than 0.020 in./lin. Ft. (0.51 mm/305 mm) |
| Static Load:             | ASTM F970 - Passes – Exceeds 250 psi                                      |
| Residual Indentation:    | ASTM F1914 - Passes - average less than 8%                                |
| Slip Resistant:          | ADA Compliant - > 0.6   |
| Resistance To Chemicals: | ASTM F925 - Passes - no change  |
| Resistance To Light:     | ASTM F1515 - Passes - less than 8 ave., max                               |
| Resistance To Heat:      | ASTM F1514 - Passes - less than 8 ave., max                               |
| Critical Radiant Flux:   | ASTM E648 - Passes - > 0.45 watts/cm <sup>2</sup> , Class 1               |
| Impact Insulation Class: | 57  |

**SUSTAINABILITY**

|                            |                       |
|----------------------------|-----------------------|
| Certification:             | FloorScore® certified |
| Biobased Material Content: | 0%                    |

**SERVICE**

|             |                            |
|-------------|----------------------------|
| Warranties: | Limited 10 Year Commercial |
|-------------|----------------------------|



132 Vera



138 Kingsley



241 Knox



322 Finn



358 Jackson



628 Lenox



758 Hermes



851 Butler



853 Emerson

Hot and Heavy Collection



958  
Cole