



**DESIGN**

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	7,111
Weight Density:	113,777
Stitches Per Inch:	10.4 (40.94 per 10 cm)
Finished Pile Thickness:	.081" (2.05 mm)
Dye Method:	Solution Dyed / Yarn Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Colorstrand® Nylon
Face Weight:	16.0 oz. per sq. yd. (542 g/m2)
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	QuarterTurn, Monolithic, BrickAshlar, VerticalAshlar, MultiDirectional
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Severe

**SUSTAINABILITY**


IAQ Green Label Plus:	Green Label Plus 1098
Pre-Consumer Recycled Content:	48%
NSF 140:	Gold
Declare Label:	Declared

**PERFORMANCE**


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

**SERVICE**

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Static
-------------	--



358  
Emerge



359  
Ecoactive



751  
Optical




859  
Cosmos




862  
Shimmer




883  
Visual



955  
Irridescent



982  
Contour



983  
Atmospheric



989  
Solar