



**DESIGN**

|                                   |  |
|-----------------------------------|--|
| Product Type:                     | <b>Broadloom</b>                       |
| Construction:                     | <b>Tufted</b>                          |
| Minimum Sq. Yd.:                  | <b>No Minimum</b>                      |
| Surface Texture:                  | <b>Textured Patterned Loop</b>         |
| Gauge:                            | <b>1/12 (47.00 rows per 10 cm)</b>     |
| Density:                          | <b>6,990</b>                           |
| Weight Density:                   | <b>139,805</b>                         |
| Stitches Per Inch:                | <b>12.0 (47.24 per 10 cm)</b>          |
| Finished Pile Thickness:          | <b>.103" (2.62 mm)</b>                 |
| Dye Method:                       | <b>Solution Dyed / Yarn Dyed</b>       |
| Backing Material:                 | <b>Unibond® Plus</b>                   |
| Fiber Type:                       | <b>Colorstrand® Nylon</b>              |
| Face Weight:                      | <b>20.0 oz. per sq. yd. (678 g/m2)</b> |
| Pattern Repeat:                   | <b>18" (W) x 39.25" L</b>              |
| Width:                            | <b>12' width (3.66 m)</b>              |
| Soil Release Technology:          | <b>Sentry Soil Protection</b>          |
| Foot Traffic Recommendation TARR: | <b>Severe</b>                          |

**SUSTAINABILITY**


|                                |                               |
|--------------------------------|-------------------------------|
| IAQ Green Label Plus:          | <b>Green Label Plus 3802</b>  |
| Pre-Consumer Recycled Content: | <b>38%</b>                    |
| NSF 140:                       | <b>Gold</b>                   |
| Declare Label:                 | <b>Declared Red List Free</b> |

**PERFORMANCE**


|                |                                       |
|----------------|---------------------------------------|
| Static:        | <b>AATCC-134 Under 3.5 KV</b>         |
| Flammability:  | <b>ASTM E 648 Class 1 (Glue Down)</b> |
| Smoke Density: | <b>ASTM E 662 Less than 450</b>       |

**SERVICE**

|             |   |
|-------------|---|
| Warranties: | <b>Lifetime Limited Unibond® Plus Warranty, Lifetime Static</b> |
|-------------|---|



358  
Emerge




359  
Ecoactive



751  
Optical




859  
Cosmos




862  
Shimmer



883  
Visual



955  
Iridescent



982  
Contour



983  
Atmospheric



989  
Solar