



DESIGN

Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	6,990
Weight Density:	139,805
Stitches Per Inch:	12.0 (47.24 per 10 cm)
Finished Pile Thickness:	.103" (2.62 mm)
Dye Method:	Solution Dyed / Yarn Dyed
Backing Material:	Unibond® Plus
Fiber Type:	Colorstrand® Nylon
Face Weight:	20.0 oz. per sq. yd. (678 g/m2)
Pattern Repeat:	18" (W) x 39.25" L
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY


IAQ Green Label Plus:	Green Label Plus 3802
Pre-Consumer Recycled Content:	38%
NSF 140:	Gold
Declare Label:	Declared Red List Free

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Unibond® Plus Warranty, Lifetime Static
-------------	---



358
Emerge



359
Ecoactive




751
Optical




859
Cosmos




862
Shimmer



883
Visual



955
Iridescent



982
Contour



983
Atmospheric



989
Solar