




Construction:	Tufted
Density:	6,990
Dye Method:	Solution Dyed / Yarn Dyed
Fiber Type:	Colorstrand® Nylon
Gauge:	1/12 (47.00 rows per 10 cm)
Product Type:	Broadloom
SmokeDensity:	ASTM E 662 Less than 450
Width:	12' width (3.66 m)
Dropped:	No
BackingMaterial:	Unibond® Plus
Declare:	Yes
FinishedPileThickness:	.103" (2.62 mm)
Flammability:	ASTM E 648 Class 1 (Glue Down)
FootTrafficRecTARR:	Severe
IAQGreenLabelPlus:	CRI Green Label Plus GLP3802
NSF140:	Unibond Plus - NSF 140 Gold
Pattern:	Graphic
PileRange:	20
Scale:	Medium
RecycledContentTotalWeight:	0.38
RecycledContentPreConsumer:	38%
SoilReleaseTechnology:	EcoSentry Soil Protection
Static:	AATCC-134 Under 3.5 KV
StitchesPerInch:	12.0 (47.24 per 10 cm)
SurfaceTexture:	Textured Patterned Loop
WeightDensity:	139,805
LaunchYear:	2016
InherentStainResistance:	Topical
Top10Corp:	No
Top10Healthcare:	No
Top10K12:	No
Top10REITI:	No
Top10Gov:	No
Top10SeniorLiving:	No
Top10HigherEd:	No
Top10Retail:	No
Declare Label:	Declared Red List Free
Pattern Repeat:	18" (W) x 39.25" L
Budget:	\$\$
CountryOfOrigin:	Ships from US
StainResistance:	EcoSentry Plus Stain Protection



358
Emerge




359
Ecoactive



751
Optical




859
Cosmos




862
Shimmer



883
Visual



955
Irridescent



982
Contour



983
Atmospheric



989
Solar