



**DESIGN**

Tufted Pile Weight:	<b>17.0 oz. per sq. yd. (576 g/m2)</b>
Product Type:	<b>Tile</b>
Construction:	<b>Tufted</b>
Minimum Sq. Yd.:	<b>No Minimum</b>
Surface Texture:	<b>Textured Patterned Loop</b>
Gauge:	<b>1/12 (47.00 rows per 10 cm)</b>
Density:	<b>6,442</b>
Weight Density:	<b>109,515</b>
Stitches Per Inch:	<b>11.0 (43.34 per 10 cm)</b>
Finished Pile Thickness:	<b>.095" (2.41 mm)</b>
Dye Method:	<b>Solution Dyed / Yarn Dyed</b>
Backing Material:	<b>EcoFlex ICT</b>
Fiber Type:	<b>Colorstrand® Nylon</b>
Pattern Repeat:	<b>Not Applicable</b>
Size:	<b>24" x 24" (.6096 m x .6096 m)</b>
Installation Method:	<b>Monolithic, Vertical Ashlar, Brick Ashlar, Quarter Turn, Multi Directional</b>
Stain Release Technology:	<b>Sentry Plus Stain Protection</b>
Soil Release Technology:	<b>Sentry Soil Protection</b>
Foot Traffic Recommendation TARR:	<b>Severe</b>

**SUSTAINABILITY**

IAQ Green Label Plus:	<b>CRI Green Label Plus GLP1098</b>
Pre-Consumer Recycled Content:	<b>48%</b>
NSF 140:	<b>EcoFlex ICT - NSF 140 Gold</b>
Declare Label:	<b>Declared</b>

**PERFORMANCE**

Static:	<b>AATCC-134 Under 3.5 KV</b>
Flammability:	<b>ASTM E 648 Class 1 (Glue Down)</b>
Smoke Density:	<b>ASTM E 662 Less than 450</b>

**SERVICE**

Warranties:	<b>Lifetime Limited Carpet Tile Warranty, Lifetime Static</b>
-------------	---



131  
Madras  
Quickship Available




585  
Sea Breeze  
Quickship Available



878  
Mudslide  
Quickship Available



968  
Smoky Martini  
Quickship Available



989  
Black Velvet  
Quickship Available