

DESIGN

<p>Tufted Pile Weight: 20.0 oz. per sq. yd. (678 g/m²)</p> <p>Product Type: Tile</p> <p>Construction: Tufted</p> <p>Minimum Sq. Yd.: No Minimum</p> <p>Surface Texture: Textured Patterned Loop</p> <p>Gauge: 1/12 (47.00 rows per 10 cm)</p> <p>Density: 8,571</p> <p>Weight Density: 171,428</p> <p>Stitches Per Inch: 10.5 (41.34 per 10 cm)</p> <p>Finished Pile Thickness: .084" (2.13 mm)</p> <p>Dye Method: Solution Dyed</p> <p>Backing Material: EcoFlex NXT</p> <p>Fiber Type: Duracolor® Tricolor Premium Nylon with metallic Duracolor</p> <p>Fiber Technology: Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet.</p> <p>Pattern Repeat: Not Applicable</p> <p>Size: 12" x 36" (.3048 m x .9144 m)</p> <p>Installation Method: Monolithic, Half Lap, Brick Ashlar, Basket Weave, Plank Half Lap, Monolithic Stepping, Random, Herringbone</p> <p>GSA Stain Release Rating: Pass</p> <p>Stain Release Technology: Permanent, Built into Fiber</p> <p>Soil Release Technology: Sentry Soil Protection</p> <p>Foot Traffic Recommendation TARR: Severe</p>

SUSTAINABILITY


<p>IAQ Green Label Plus: CRI Green Label Plus GLP1171</p> <p>Pre-Consumer Recycled Content: 56%</p> <p>NSF 140: EcoFlex NXT - NSF 140 Gold</p> <p>Declare Label: Declared Red List Free</p>

PERFORMANCE

<p>Static: AATCC-134 Under 3.5 KV</p> <p>Flammability: ASTM E 648 Class 1 (Glue Down)</p> <p>Smoke Density: ASTM E 662 Less than 450</p>
--

SERVICE

<p>Warranties: Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static</p>
--




138 Sulpher



576 Lagoon



739 Glacier



856 Sediment



869 Alpine



949 Fossil



955 Coastal



978 Mineral