



**DESIGN**


|                                   |  |
|-----------------------------------|--|
| Tufted Pile Weight:               | 20.0 oz. per sq. yd. (678 g/m <sup>2</sup> )   |
| Product Type:                     | Tile   |
| Construction:                     | Tufted   |
| Minimum Sq. Yd.:                  | No Minimum   |
| Surface Texture:                  | Textured Patterned Loop  |
| Gauge:                            | 1/12 (47.00 rows per 10 cm)  |
| Density:                          | 8,000  |
| Weight Density:                   | 160,000  |
| Stitches Per Inch:                | 11.5 (45.28 per 10 cm)   |
| Finished Pile Thickness:          | .090" (2.29 mm)  |
| Dye Method:                       | Solution Dyed  |
| Backing Material:                 | EcoFlex NXT  |
| Fiber Type:                       | Duracolor® Tricor Premium Nylon  |
| Fiber Technology:                 | Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet. |
| Pattern Repeat:                   | Not Applicable   |
| Size:                             | 24" x 24" (.6096 m x .6096 m)  |
| Installation Method:              | Quarter Turn, Monolithic, Brick Ashlar, Vertical Ashlar, Multi Directional   |
| GSA Stain Release Rating:         | Pass   |
| Stain Release Technology:         | Permanent, Built into Fiber  |
| Soil Release Technology:          | Sentry Soil Protection   |
| Foot Traffic Recommendation TARR: | Severe   |



364  
Wine




454  
Lavender



556  
Blue



575  
Navy



656  
Green



846  
Teak



869  
Medium Taupe



889  
Dark Taupe



929  
Light Grey

**SUSTAINABILITY**

|                                |                              |
|--------------------------------|------------------------------|
| IAQ Green Label Plus:          | CRI Green Label Plus GLP1171 |
| Pre-Consumer Recycled Content: | 56%                          |
| NSF 140:                       | EcoFlex NXT - NSF 140 Gold   |
| Declare Label:                 | Declared Red List Free       |

**PERFORMANCE**

|                |                                |
|----------------|--------------------------------|
| Static:        | AATCC-134 Under 3.5 KV         |
| Flammability:  | ASTM E 648 Class 1 (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450       |

**SERVICE**


|             |   |
|-------------|---|
| Warranties: | Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static |
|-------------|---|



955  
Medium Cool Grey



968  
Medium Grey



979  
Black



985  
Dark Cool Grey



989  
Dark Grey