Mohawk Group

Living Local Collection



123	141	142
Western Woods	Gold	Sable
332	342	358
Cedar	Down Town	Brick
363	372	812
Regal Red	Suede	Tan Tone

DESIGN

Product Type: Floating LVT
Gauge: 4.5mm

Wear Layer: 20 mil (0.5mm)

Finish: M-Force Enhanced Urethane

148.4mm x 1214.1mm (actual) 5.84"W x 47.8"L

(nominal)

Square Feet Per Carton: 19.39 sf/ctn
Pieces Per Carton: 60 cartons/pallet
Pounds per carton: 30.6 lbs/ctn

Installation Method: Floating LVT with Uniclic Locking System

Underlayment: Mohawk ActiveSound™ (Optional)

PERFORMANCE

Construction: Commercial grade luxury vinyl tile

Classification: ASTM F1700 - Class III, Type A - Smooth, Type B -

Embossed

Squareness: ASTM F2055 - Passes - 0.010 in. max

Size and Tolerance: ASTM F2055 - Passes - \pm 0.016 in. per linear foot Thickness: ASTM F386 - Passes - As Specified \pm 0.005 in. Flexibility: ASTM F137 - Passes - \leq 1.0 in., no cracks or breaks Dimensional Stability: ASTM F2199 - Passes - \leq 0.020 in. per linear foot

Static Load: ASTM F970 - Passes, modified - 1000 psi

Residual Indentation: ASTM F1914 - Passes - Average less than 8%

Slip Resistant: ASTM C1028 - Passes \geq 0.5
Resistance To Chemicals: ASTM F925 - Passes - No Change
Resistance To Light: ASTM F1515 - Passes - $\Delta E \leq 8$

Resistance To Heat: ASTM F1514 - Passes - $\Delta E \le 8$

Critical Radiant Flux: ASTM E648 - Passes - ≥ 0.45 watts/cm2, Class 1

Smoke Density: ASTM E662 Part A - Passes - < 450

SUSTAINABILITY

Certification: FloorScore® certified

SERVICE

Warranties: Limited 10 Year Commercial



Living Local Collection



918

Silver