



DESIGN

| | |
|-----------------------------------|---|
| Woven Pile Weight: | 45.0 oz. per sq. yd. (1526 g/m ²) |
| Product Type: | Woven |
| Construction: | Woven |
| Minimum Sq. Yd.: | No Minimum |
| Surface Texture: | Textured Patterned Loop |
| Density: | 9,358 |
| Weight Density: | 421,110 |
| Pitch: | 216 (315 ends per meter) |
| Rows Per Inch: | 7.8 (30.71 per 10 cm) |
| Finished Pile Thickness: | .178" (4.52 mm) |
| Dye Method: | Solution Dyed / Yarn Dyed |
| Backing Material: | Woven |
| Fiber Type: | Colorstrand® Nylon |
| Pattern Repeat: | .75" (W) x .75" (L) |
| Width: | 12' width (3.66 m) |
| Stain Release Technology: | Sentry Plus Stain Protection |
| Soil Release Technology: | Sentry Soil Protection |
| Foot Traffic Recommendation TARR: | Severe |

SUSTAINABILITY

| | |
|--------------------------------|------------------------------|
| IAQ Green Label Plus: | CRI Green Label Plus GLP3802 |
| Pre-Consumer Recycled Content: | 15% |
| NSF 140: | Woven - NSF 140 Gold |
| Declare Label: | Declared Red List Free |

PERFORMANCE


| | |
|----------------|--------------------------------|
| Static: | AATCC-134 Under 3.5 KV |
| Flammability: | ASTM E 648 Class 1 (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450 |

SERVICE

| | |
|-------------|---|
| Warranties: | Lifetime Limited Woven Wear Warranty, Lifetime Static |
|-------------|---|



137
Ravel



168
Weave



658
Knit



888
Cord



959
Twist



979
Braid



989
Tangle