



DESIGN


Tufted Pile Weight:	15 oz/yd ² (509 g/m ²)
Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	6,585
Weight Density:	98,780
Stitches Per Inch:	11.0 (43.31 per 10 cm)
Finished Pile Thickness:	.082" (2.08 mm)
Dye Method:	Solution Dyed
Backing Material:	EcoFlex Matrix
Fiber Type:	Colorstrand® SD Nylon
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	Quarter Turn, Monolithic, Vertical Ashlar, Brick Ashlar, Multi Directional
Stain Release Technology:	Sentry Plus Stain Protection
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Heavy



593
Navy Gray
Quickship Available




929
Light Elm
Quickship Available



937
Steel
Quickship Available



948
Brown Oak
Quickship Available



979
Pencil Lead
Quickship Available



989
Charcoal
Quickship Available

SUSTAINABILITY

IAQ Green Label Plus:	CRI Green Label Plus GLP1171
Pre-Consumer Recycled Content:	53%
NSF 140:	EcoFlex Matrix - NSF 140 Gold
Declare Label:	Declared Red List Free

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Colorfastness to Atmospheric Contaminants, 10 Year Stain Warranty, 10 Year Limited Static
-------------	---