



DESIGN

| | |
|-----------------------------------|--|
| Tufted Pile Weight: | 14.0 oz. per sq. yd. (474 g/m ²) |
| Product Type: | Tile |
| Construction: | Tufted |
| Minimum Sq. Yd.: | No Minimum |
| Surface Texture: | Level Patterned Loop |
| Gauge: | 1/12 (49.00 rows per 10 cm) |
| Density: | 5,929 |
| Weight Density: | 83,012 |
| Stitches Per Inch: | 10.3 (40.55 per 10 cm) |
| Finished Pile Thickness: | .085" (2.16 mm) |
| Dye Method: | Solution Dyed |
| Backing Material: | EcoFlex ICT |
| Fiber Type: | Colorstrand® SD Nylon |
| Pattern Repeat: | Not Applicable |
| Size: | 24" x 24" (.6096 m x .6096 m) |
| Installation Method: | Monolithic, Vertical Ashlar, Quarter Turn, Brick Ashlar, Multi Directional |
| Stain Release Technology: | Sentry Plus Stain Protection |
| Soil Release Technology: | Sentry Soil Protection |
| Foot Traffic Recommendation TARR: | Heavy |

SUSTAINABILITY

| | |
|--------------------------------|------------------------------|
| IAQ Green Label Plus: | CRI Green Label Plus GLP1098 |
| Pre-Consumer Recycled Content: | 48% |
| NSF 140: | EcoFlex ICT - NSF 140 Gold |
| Declare Label: | Declared |

PERFORMANCE

| | |
|----------------|--------------------------------|
| Static: | AATCC-134 Under 3.5 KV |
| Flammability: | ASTM E 648 Class 1 (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450 |

SERVICE

| | |
|-------------|--|
| Warranties: | Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static |
|-------------|--|



7238
Pumice
Quickship Available



7358
Breccia



7559
Opal
Quickship Available



7568
Marble
Quickship Available



7656
Gabbro



7688
Ore
Quickship Available




7728
Chert
Quickship Available



7858
Feldspar



7879
Basalt
Quickship Available



7927
Shale
Quickship Available



7948
Granite
Quickship Available