Mohawk Group

BT286 First One Up Tile

Mohawk Group



DESIGN

Tufted Pile Weight:	**22.0 oz. per sq. yd. (746 g/m2)**
Product Type:	**Tile**
Construction:	**Tufted**
Minimum Sq. Yd.:	**No Minimum**
Surface Texture:	**Textured Patterned Loop**
Gauge:	**1/12 (47.00 rows per 10 cm)**
Density:	**7,266**
Weight Density:	**159,852**
Stitches Per Inch:	**9.0 (35.43 per 10 cm)**
Finished Pile Thickness:	**.109" (2.77 mm)**
Dye Method:	**Solution Dyed**
Backing Material:	**EcoFlex ICT**
Fiber Type:	**Colorstrand® SD Nylon**
Pattern Repeat:	**Not Applicable**
Size:	**24" x 24" (.6096 m x .6096 m)**
Installation Method:	**Monolithic, Vertical Ashlar, Brick Ashlar, Quarter Turn, Multi Directional**
Soil Release Technology:	**Sentry Soil Protection**
Foot Traffic Recommendation TARR:	**Severe**

SUSTAINABILITY

IAQ Green Label Plus:	**CRI Green Label Plus GLP1098**
Pre-Consumer Recycled Content:	**47%**
NSF 140:	**EcoFlex ICT - NSF 140 Gold**
Declare Label:	**Declared**

PERFORMANCE

Static:	**AATCC-134 Under 3.5 KV**
Flammability:	**ASTM E 648 Class 1 (Glue Down)**
Smoke Density:	**ASTM E 662 Less than 450**

SERVICE

Warranties:	**Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static**



7343
Endless



7555
Celestial



7728
Physical



7737
Civil



7767
Eternity



7828
Worldly



7868
Transitory



7969
Logic